

80.034

## UV VARNISH

### PRODUCT DESCRIPTION

U.V. curing varnish to be applied by screen printing specially designed to print on papers, cards and cardboard. High adhesion on difficult materials such as PE or PP laminates and offset inks has been obtained. The formed film, once it has been cured has a high level of flexibility which permits die cutting afterwards.

### Recommended applications:

Papers, cards and cardboard, laminated or not, offset inks.

### Finish:

Gloss. There is a matt version.

### Presentation:

It is ready for use with screens of 150-180 meshes/cm at 20°C.

### Drying:

Under 80 W U.V. lamp, it superates the talc trial at speeds of 40-50 m/min.

### Viscosity in DIN 4 cup (seconds)

75s a 25.4 °C.

### Emulsions and meshes:

Emulsion with ARGAZOL-UV with meshes from 150 to 165 meshes/cm.

The information supplied is a result of our updated knowledge; it is supplied with good intention but under no circumstances it can be taken as a guarantee. Moreover, taking into account the great diversity of printable materials, the diversity of machinery and procedures to carry out the jobs, it is the user's responsibility to check the suitability of our products to obtain the objectives he desires, with the resources and procedures he has. The user must also be make sure he complies with the current legislation, situation of patents and third party rights when applicable.